

SUPERGLOSS SW SPECIAL PERMANENT "N"

DESCRIPTION

Face stock :

White woodfree cast coated paper with mirror finish and high whiteness level. Excellent printing quality by all common print processes such as offset, letterpress, screen, flexo, gravure and hot foil stamping.

Weight	ca. 80 g/m ²	ISO 536
Thickness	Min. 80 µm	ISO 534
BEKK smoothness	Min. 500 sec.	ISO 5627
Opacity (with adhesive)	Min. 89 %	ISO 2471

Adhesive :

Permanent rubber, hot melt adhesive, high-performance specially developed for applications on difficult surfaces : PE, PP, PS, fibrous, rough or curved surfaces.

Backing :

White coated Kraft paper ca. 95 g/m² : pre-scored backing (with mechanically scored breaklines ca. 31,5 mm apart), no back printing (Starliner NBP)

Laminate :

ca. 200 (STARliner NBP) g/m²

ADHESIVE

	Tack	Adhésion
SPECIAL PERMANENT : High tack adhesive specially developed for applications on difficult surfaces	●●●	●●●
	●● : Medium	● : Low

●●● : High

●● : Medium

● : Low

Temperature ranges

Min. application temperature : - 5 °C

Service temperature : - 15 °C to + 70 °C

Food contact

Direct contact dry and moist non fatty foodstuff (24179 U 07)

Shelf life

2 years when stored at 15-25 °C, (50 ± 5) % relative humidity, in the original packaging.

APPLICATIONS AND USES

For top quality print jobs and multicolour labels for application on difficult substrates. Allows creations of impressive visual appearance. Luxury labels, personalised items, business cards, greeting cards, ...

MAIN BENEFITS FOR THE USER

Outstanding Printing Quality.

Perfect flatness thanks to the outstanding dimensional stability due to the conditioning of the complex at 21 +2 °C and at ca. 55+-10 % relative humidity.

Complementary facility with STARliner® backing: no need of backslitting thanks to pre-scored lines.

GENERAL REMARK : factors affecting adhesion

Adhesion failure problems can be avoided by :

- Where possible, always test the proposed construction under actual application and end-use conditions because a 100 % multi-purpose adhesive for all substrates does not exist.
Adverse reactions may occur when applying Removable adhesive onto certain substrates. Therefore, a suitability test is necessary.
- Being familiar with factors which adversely affect adhesion :
- Labels or stickers should not be applied onto dusty, dirty, oily or oxidized surfaces.
- Mould release agents on blow-moulded plastic surfaces inhibit adhesion.
- Adhesion failure may occur on substrates with low surface tension, such as polyethylene or polypropylene. Rubber based adhesives stick better to low energy surfaces than acrylics.
- Avoid the use of relatively rigid facestocks on highly curved or small diameter surfaces.

Do not use pressure sensitive materials outside the recommended service temperature range, or do not apply below the minimum application temperature.



MACtac Europe
Bd Kennedy, Zoning Industriel, Zone B
B-7060 Soignies Belgium
Phone : +32 (0) 67 346 211
Fax : +32 (0) 67 346 339
www.mactac-europe.com
e-mail : mactac.europe@mactac.com



All MACtac products are subject to careful quality control throughout the manufacturing process and are warranted to be of quality and free from manufacturing defects.

Published information concerning MACtac products is based upon research which the Company believes to be reliable although such information does not constitute a warranty.

Because of the variety of uses of MACtac products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.